



CLASSIC AC SERIES

SALT WATER ELECTROLYSERS
CHLORINE GENERATORS

- Non-reverse polarity
- Powered by transformer power supply
- Salinity 5,000 ppm
- Warranty: Residential application - 3 years, Commercial application - 1 year

MODEL	CHLORINE	INPUT AC POWER CONSUMPTION	WATER FLOW	DIMENSION (PACKAGED)	WEIGHT GROSS
	Grams / Hour	kW	Litres / Minute	L x W x H (cm)	Kg
ACMINI	5	0.070	200 - 400	39 x 35 x 26	11
AC15	15	0.215	200 - 400	39 x 35 x 26	11
AC20	20	0.290	200 - 400	39 x 35 x 26	11
AC25	25	0.360	200 - 400	39 x 35 x 26	11
AC35	35	0.505	200 - 400	43 x 33 x 27	27
AC50	50	0.540	200 - 400	43 x 33 x 27	27
AC50HD	50 With Heavy Duty Grade Electrodes	0.720	200 - 400	43 x 33 x 27	27

OPTIONS (AVAILABLE TO AUSTRALIAN CUSTOMERS ONLY)

PREFIX	DESCRIPTION	ADDITIONS AVAILABLE FOR
T	Timer Option	Mini/15/20/25/35/50/50HD
QT	Timer With Battery Back Up	Mini/15/20/25/35/50/50HD
L12	Underwater Light Option 12V	Mini/15/20/25
L24	Underwater Light Option 24V	Mini/15/20/25
L32	Underwater Light Option 32V	Mini/15/20/25

